



Item P20-0019

Fire Rated Access Doors For Walls & Ceilings

Insulated fire rated door for drywall, masonry or plaster. Rated by Underwriters Laboratories for a 1.5 hour "B" label fire rating in walls and by Warnock Hersey for 3 hours in ceilings and 2 hours in walls. Door panel contains two inches of insulation in sandwich type construction and swings easily to 175° on a continuous hinge. Doors are furnished with automatic closers and are self-latching. Interior latch release allows the door to be opened from the inside. Frame is fabricated for 16 gauge, galvanized steel with prime coat finish and provided with masonry anchors and bolt holes. Prime coated steel finish. **More sizes and styles available, including stainless steel. Call for a complete listing. Manufactured by Elmdor.**

Item	Description	Attributes
20-0019		Door Size W x H: 8" x 8" Wall Or Ceiling Opening: 8 3/8" x 8 3/8" No. of Stud Latches: 1
20-0020		Door Size W x H: 12" x 12" Wall Or Ceiling Opening: 12 3/8" x 12 3/8" No. of Stud Latches: 1
20-0022		Door Size W x H: 18" x 18" Wall Or Ceiling Opening: 18 3/8" x 18 3/8" No. of Stud Latches: 1
20-0024		Door Size W x H: 24" x 24" Wall Or Ceiling Opening: 24 3/8" x 24 3/8" No. of Stud Latches: 1
20-0026		Door Size W x H: 16" x 16" Wall Or Ceiling Opening: 16 3/8" x 16 3/8" No. of Stud Latches: 1
20-0242		Door Size W x H: 14" x 14" Wall Or Ceiling Opening: 14 3/8" x 14 3/8" No. of Stud Latches: 1