



Item P21-0861

Kindorf® Pipe Straps

Kindorf® Pipe Straps are designed to be twist inserted anywhere along the slot side of the channel. Pipes can be placed as closely as pipe couplings permit. Unique feature of the strap include bolt head is combination slot and hex head for flexibility of attachment. Square nut is captivated on the shoulder for easy one-handed tightening. Straps are interchangeable with 1-5/8" strut for broader application. Galv-Krom® finish.

Item	Description	Attributes
21-0861		Ridgid Conduit or Pipe Size: 3/4" O.D. Size (in.): 1.050 Steel Strap Thickness: 14 ga Design Load (lbs.): 750
21-0854		Ridgid Conduit or Pipe Size: 1" O.D. Size (in.): 1.315 Steel Strap Thickness: 14 ga Design Load (lbs.): 750
21-0858		Ridgid Conduit or Pipe Size: 2-1/2" O.D. Size (in.): 2.875 Steel Strap Thickness: 12 ga Design Load (lbs.): 1000
21-0859		Ridgid Conduit or Pipe Size: 3" O.D. Size (in.): 3.500 Steel Strap Thickness: 12 ga Design Load (lbs.): 1650
21-0860		Ridgid Conduit or Pipe Size: 3-1/2" O.D. Size (in.): 4.000 Steel Strap Thickness: 11 ga Design Load (lbs.): 1650
21-0862		Ridgid Conduit or Pipe Size: 4" O.D. Size (in.): 4.500 Steel Strap Thickness: 11 ga Design Load (lbs.): 1650
21-0863		Ridgid Conduit or Pipe Size: 5" O.D. Size (in.): 5.563 Steel Strap Thickness: 11 ga Design Load (lbs.): 1650