



Item P16-0231

Nu-Wave Scaffold Systems

Nu-Wave scaffold roll through standard commercial doorways without dismantling. One person can assemble without tools and adjust platform height in 4" increments in a matter of seconds. Holes on both sides of the end frame aid in ease of assembly. Solid steel stack pins secure stacked units. 5" Casters feature a unique expansion ring; no ring required to secure caster. Casters roll easily, are heavy duty and have a dual locking mechanism. Meets OSHA and ANSI requirements. Load capacity 1,000 lbs. Units may be stacked to a maximum of 18 ft when a set of (4) outriggers and a guardrail kit with toeboards are installed. 29-1/2" wide end frame access ladders, provide a safe access to work platforms.

Complete unit consists of:

(1) 69 ½" Ladder, Platform and trusses

(1) Guardrail Kit

(1) 20" Outrigger

(8) 5" locking casters

Item	Description	Attributes
16-0231	6' Rolling Scaffold System Complete	
16-0232	8" Rolling Scaffold System Complete	
16-0203	69 ½" Ladder, 4' Platform and Trusses	
16-0204	69 ½" Ladder, 6' Platform and Trusses	
16-0205	69 ½" Ladder, 8' Platform and Trusses	
16-0206	Guardrail Kit – 6' Scaffold	
16-0207	Guardrail Kit – 8' Scaffold	
16-0208	20" Outrigger (4 required, casters not included)	
16-0211	6' Classic Platform (28.5" w x 70.25" L)	
16-0212	40" Ladder, 3 rungs	
16-0213	5" Locking Replacement Caster (no pin required to secure casters)	
16-0214	5" Economy replacement locking casters	