



Item P12-2287

Portable Electric Salamander

Designed for construction site heating, or emergency heating and drying. 10" rubber wheels for easy mobility. Safety yellow heater enclosure has safety screens on both air intake and output openings. Long-life finned tubular heating elements, high-limit thermal cutout switch with automatic reset. Thermostat adjusts from 40° to 100° F. Toggle switch for fan only operation. Salamander units are factory pre-wired for 3-phase delta operation. The units can be converted to Single Phase operation. However, please note that conversion to single phase voids C-UL®, UL®, and ETL Listings. 800 CFM. Weight: 51 lbs. Cable kit must be ordered separately, except for **Item 12-2292**, 10 foot cord comes preassembled.

Item	Description	Attributes
12-2285		BTU: 51,195 Volts: 208 Phase: 3 Amps: 42 Wire Size @ 50 ft. -Use Industrial Grade SO Cable: 6/4 Plug- Min Amp Rating: 50 Cable Kit: 12-3041
12-2287		BTU: 51,195 Volts: 240 Phase: 3 Phase Amps: 36 Wire Size @ 50 ft. -Use Industrial Grade SO Cable: 6/4 Plug- Min Amp Rating: 50 Cable Kit: 12-3041
12-2294		BTU: 51,195 Volts: 240 Phase: 1 Phase Amps: 63 Wire Size @ 50 ft. -Use Industrial Grade SO Cable: 4/3 Plug- Min Amp Rating: 100 Cable Kit: 12-3042
12-2289		BTU: 51,195 Volts: 480 Phase: 3 Phase Amps: 18 Wire Size @ 50 ft. -Use Industrial Grade SO Cable: 12/4 Plug- Min Amp Rating: 20 Cable Kit: 12-3043
12-2292		BTU: 34,130 Volts: 240 Phase: 1 Phase Amps: 42 Wire Size @ 50 ft. -Use Industrial Grade SO Cable: 6/3 Plug- Min Amp Rating: 50 Cable Kit: Factory Installed