



TOOLS & EQUIPMENT ■ SUPPLIES ■ SAFETY PRODUCTS ■ TOOL REPAIR ■ RENTALS

Item P99-8130

PowerFoam™

PRODUCT DESCRIPTION

PowerFoam™ is a normal expansion polyurethane foam sealant which is supplied with a handy straw applicator. No special dispensing gun is necessary for use. Adheres to wood, metal, masonry and concrete. Seals gaps and joints, insulates, stops air infiltration and saves time and money. Ideal for use around pipes, wires and ductwork.

APPLICATIONS

PowerFoam™ is dispensed through a convenient straw applicator. Ideal for smaller jobs and one time use. Voids should be filled approximately 30-40% to allow for the final expansion of the foam. Recommended minimum curing time is 24 hours prior to scraping or painting.

TYPICAL USES

Insulating

• Floor / wall joints • Electrical junction boxes • Attics • Refrigeration units and pipes • Air conditioning systems

Filling

• Breaches in walls • Pipe penetrations in non-fire-rated walls • Voids in concrete forms • Underground utility ductwork • Sound dampening

Item	Description	Attributes
99-8130		Size: PowerFoam 12 oz. Std.Box: 12
99-8132		Size: PowerFoam 29 oz. Std.Box: 12