

## Item P19-1443

### Propane Forced Air Heaters

Rugged two-piece spigot barrel, designed to make cleaning and maintenance easier and safer. Continuous electronic ignition is always present as a source of ignition for unburned fuel, reducing the ability for fuels to pool and collect in a dangerous manner. Solid spark ignition. **Includes: L.P. Hose and regulator.**

Item	Description	Attributes
19-1443		<b>BTU / Hour:</b> 35,000 - 65,000 <b>Output:</b> 300 cfm <b>Heating Area:</b> 1,250 sq. ft. <b>Run Time:</b> 7 hours <b>Mainimum Tank Size:</b> 20 lbs. <b>Hose Length:</b> 15'
19-1444		<b>BTU / Hour:</b> 125,00-170,000 <b>Output:</b> 450 cfm <b>Heating Area:</b> 3,500 sq. ft. <b>Run Time:</b> 17 Hours <b>Mainimum Tank Size:</b> 100 lbs <b>Hose Length:</b> 20' <b>Details:</b> • Equipped with a 25°F - 95°F thermostat. The heating element cycles on an doff to maintain the set temperature
19-1006		<b>BTU / Hour:</b> 400,000 <b>Output:</b> 1,400 CFM <b>Heating Area:</b> 9,000 sq ft. <b>Run Time:</b> 17 Hours <b>Mainimum Tank Size:</b> 100 lbs. <b>Hose Length:</b> 20' <b>Details:</b> Includes Built-In Thermostat