



Item P13-0318

Site Drainer Pit Boss - Internal Vertical Float

Portable and lightweight yet rugged enough for the toughest jobs. Patented stainless-steel cage with ¼" openings that surrounds the pump preventing rocks, rope, and other debris from clogging the pump impeller, rendering trouble-free, long lasting operation. Top discharge provides maximum motor cooling efficiency allowing continuous duty operation at low water levels and extended dry-run capability. Pumps up to 4980 gallons per hour at 5 ft. lift, emptying sump pit in seconds. **Integrated vertical float** allows for auto on operation at 7" of water, auto off operation at 2" of water. Pump motor is housed in watertight casing, conforms to class F insulation; 110-Volts motor, draws 10.7 Amps. Motor has a built-in thermal protector which protects against overheating and extended dry run. 33 ft. power cord, 2" male discharge flange, easy-to-grip handle makes this pump easily portable. Perfect for Elevator Shaft Sump Pit, as per National Elevator Code: ANSI A17.1.

Specifications	
HP	1
Running Amps	10.7
Power Cord	33 ^ ^
Discharge Connection	2" NPT
Weight	33 lbs
Dimensions	11" Dia x 14.25"H

Item	Description	Attributes
13-0318	Site Drainer Pit Boss 102 V	