



Item P12-1488

Site Drainer™ Pit Boss - Knotted Fireman's Rope

Fully assembled, ready to use; offers drop and go, no-clogging performance. Discharge Size 2" NPT. Patented stainless-steel cage with ¼" openings that surrounds the pump preventing rocks, rope, and other debris from clogging the pump impeller, rendering trouble-free, long-lasting operation. Pumps up to 4980 gallons per hour at 5 ft. lift, emptying sump pit in seconds. Knotted Fireman's Rope allows for easy deployment and retrieval without damaging the power cord. Pump motor is housed in watertight casing, conforms to class F insulation; 110-Volts motor, draws 10.7 Amps. Motor has a built-in thermal protector which protects against overheating and extended dry run. 33 ft. power cord, 2" male discharge flange, easy-to-grip handle makes this pump easily portable.

Site Drainers™ patented "free flow design cylinder" technology is unlike that of any other electric submersible dewatering pump on the market. Where other pumps will fail Site Drainers™ allows the water to continue to flow freely even after a solid particle barrier is created. It simply will not clog.

Specifications	
HP	1
Running Amps	10.7
Power Cord	33 ^ ^
Discharge Connection	2" NPT
Weight	33 lbs
Dimensions	8.5"Dia x 13.25"H

Item	Description	Attributes
12-1488	Site Drainer™ Pit Boss 102 R	