



**Item P12-4016**

**Smith Heavy Duty Regulators**

Tough forged brass body and bonnet are designed for years of on-the-job service and provide durability for service in corrosive atmospheres. Heavy duty construction provides long trouble-free operation; brass bonnet features colorcoded label for easy gas identification. Reverse flow check valves are installed on oxygen and fuel gas cylinder regulators to protect against reverse flow of gases. The oxygen ( **Item 12-4014**) and acetylene (**Item 12-4016**) regulators come with Hard Hat™ Gauge Guard which helps prevent broken gauges which can lead to gas leaks, costly repairs and expensive down time. Replacement Gauges also available (see chart). **Our Replacement Gauges can be used with other brands of regulators.**

Item	Description	Attributes
12-4014		<b>Gas Used:</b> Oxygen <b>Inlet Connection:</b> Female CGA540 <b>Gauge Diameter:</b> 2 1/2"
12-4016		<b>Gas Used:</b> Acetylene <b>Inlet Connection:</b> Female CGA300 <b>Gauge Diameter:</b> 2 1/2"
12-4134	Gauges (Inlet) Replacement	<b>Max PSI:</b> 4,000
12-4136	Gauges (Outlet) Replacement	<b>Max PSI:</b> 200
12-4138	Gauges (Inlet) Replacement	<b>Max PSI:</b> 400
12-4140	Gauges (Outlet) Replacement	<b>Max PSI:</b> 30