



Item P11-6140

Wilton Carriage Clamps

High tensile ductile alloy casting. Hardened steel spindle. Patented Perma-Pads® are guaranteed never to come off.

Item	Description	Attributes
11-6140		Capacity: 0 - 2 1/2" Throat Depth: 1 3/4" Spindle Diameter: 1/2" Minimum Proof Test Lbs.: 1,100
11-6141		Capacity: 0 - 3" Throat Depth: 1 7/8" Spindle Diameter: 1/2" Minimum Proof Test Lbs.: 1,800
11-6142		Capacity: 0 - 4" Throat Depth: 2 1/16" Spindle Diameter: 5/8" Minimum Proof Test Lbs.: 2,150
11-6143		Capacity: 0 - 6" Throat Depth: 2 3/4" Spindle Diameter: 5/8" Minimum Proof Test Lbs.: 2,450
11-6144		Capacity: 0 - 8" Throat Depth: 3 1/4" Spindle Diameter: 3/4" Minimum Proof Test Lbs.: 2,750
11-6145		Capacity: 0 - 10" Throat Depth: 3 5/8" Spindle Diameter: 7/8" Minimum Proof Test Lbs.: 2,850
11-6146		Capacity: 0 - 12" Throat Depth: 3 5/8" Spindle Diameter: 7/8" Minimum Proof Test Lbs.: 2,850