

## Item P16-0170

### Casters

These high quality casters undergo rigorous testing to deter mine wear resistance, temperature resistance, and load capacities. Composition rubber wheel combines a soft rubber tread with a hard rubber core for quiet movement, a cushioned ride, and maximum floor protection. Casters are self-lubricating.

Item	Description	Attributes
16-0170		<b>Diameter:</b> 2 1/2" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 1 1/8" <b>Axle Size:</b> 5/16" <b>Load Capacity:</b> 150 lbs. <b>Overall Height:</b> 3 1/4" <b>Mounting Bolt Dia.:</b> 5/16"
16-0171		<b>Diameter:</b> 2 1/2" <b>Caster Style:</b> Rigid <b>Tread Width:</b> 1 1/8" <b>Axle Size:</b> 5/16" <b>Load Capacity:</b> 125 lbs. <b>Overall Height:</b> 3 1/4" <b>Mounting Bolt Dia.:</b> 5/16"
16-0172		<b>Diameter:</b> 3" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 250 lbs. <b>Overall Height:</b> 3 13/16" <b>Mounting Bolt Dia.:</b> 5/16"
16-0169		<b>Diameter:</b> 3" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 250 lbs. <b>Overall Height:</b> 3 13/16" <b>Mounting Bolt Dia.:</b> 5/16" <b>Details:</b> *
16-0173		<b>Diameter:</b> 3" <b>Caster Style:</b> Rigid <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 250 lbs. <b>Overall Height:</b> 3 13/16" <b>Mounting Bolt Dia.:</b> 5/16"
16-0174		<b>Diameter:</b> 4" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 255 lbs. <b>Overall Height:</b> 5" <b>Mounting Bolt Dia.:</b> 5/16"
16-0175		<b>Diameter:</b> 4" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 300 lbs. <b>Overall Height:</b> 5" <b>Mounting Bolt Dia.:</b> 5/16" <b>Details:</b> *

16-0176		<b>Diameter:</b> 4" <b>Caster Style:</b> Rigid <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 300 lbs. <b>Overall Height:</b> 5" <b>Mounting Bolt Dia.:</b> 5/16"
16-0177		<b>Diameter:</b> 5" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 250 lbs. <b>Overall Height:</b> 6 1/8" <b>Mounting Bolt Dia.:</b> 5/16"
16-0178		<b>Diameter:</b> 5" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 250 lbs. <b>Overall Height:</b> 6 1/8" <b>Mounting Bolt Dia.:</b> 5/16" <b>Details:</b> *
16-0179		<b>Diameter:</b> 5" <b>Caster Style:</b> Rigid <b>Tread Width:</b> 1 1/4" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 250 lbs. <b>Overall Height:</b> 6 1/8" <b>Mounting Bolt Dia.:</b> 5/16"
16-0180		<b>Diameter:</b> 8" <b>Caster Style:</b> Rigid <b>Tread Width:</b> 2" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 600 lbs. <b>Overall Height:</b> 9 1/2" <b>Mounting Bolt Dia.:</b> 5/16"
16-0182		<b>Diameter:</b> 8" <b>Caster Style:</b> Swivel <b>Tread Width:</b> 2" <b>Axle Size:</b> 3/8" <b>Load Capacity:</b> 600 lbs. <b>Overall Height:</b> 9 1/2" <b>Mounting Bolt Dia.:</b> 5/16"

\*with Rollock Brake

#### Other Casters

Let us quote on any of your special caster requirements.

